



Cert. No. LRQ 0963008

ISO 9001

spirax/sarco

TI-P403-25

AB Issue 4

MS1 Conductivity Meter

- Automatic temperature compensation
- Wide selectable range
- Automatic switch-off

Description

The Spirax Sarco MS1 is a battery powered conductivity meter designed for use with liquids. It is particularly suitable for measuring the conductivity of boiler water, feed water, or condensate samples in order to estimate the level of Total Dissolved Solids, or TDS.

The instrument is fitted with a permanently wired carbon electrode sensor with integral temperature sensor.

A plug-in extension lead is also provided to allow ac resistance measurements to be made on installed conductivity probes in order to check their condition. Calibration to a master instrument or standard solution is possible using the adjustment screw on the side of the case. The instrument is supplied in a protective wallet.

Limiting conditions

Maximum recommended sensor operating temperature 45°C.

Specification

	0 to 1.999 $\mu\text{S/cm}$
Ranges	0 to 19.99 $\mu\text{S/cm}$
	0 to 199.9 $\mu\text{S/cm}$
Range indication	Decimal point and LED above selection key
Temperature compensation	Automatic, 2%/°C
	Reference temperature 25°C
Resolution	0.1 $\mu\text{S/cm}$
Accuracy	$\pm 1.5\%$ or ± 3 digits (whichever is greatest) at 25°C
Calibration range	$\pm 20\%$. 20 turns (approximately)
On/off	Auto-off timer
Sensor	PVC cell with carbon electrodes
Extension cable	Twin core
	3.5 mm jack plug and crocodile clips
Battery	PP3 or equivalent
	A low battery warning indicator is fitted

Dimensions/weight (approximate) in mm and kg

Instrument	80 x 147 x 39
Sensor	140 x 21 diameter
Sensor cable	1000
Extension cable	1000
Weight	430 g with case

How to order

Example: 1 off Spirax Sarco MS1 conductivity meter.

