STERI-TROL

Clean service control valves











STERI-TROL

The smart, flexible option

About the STERI-TROL

Clean service applications demand the very best in valve performance and product design. With Spirax Sarco as your supplier, you can be confident that you are getting the best possible solution for your application. You can trust us to meet your requirements exactly, and to provide control valves that will not let you down.

The STERI-TROL is a pneumatically-operated, 2-port angle pattern, clean service control valve that features:

- 316L stainless steel construction
- PN16 rating
- 170°C maximum operating temperature
- Modulating and on/off control
- All industry standard connections
- Standard and customer-defined centre face dimensions
- Industry standard control interface devices, including stainless steel positioner

Industries and applications

- Pharmaceuticals
- Biotechnology
- Semi-conductor
- Food
- Brewing and beverages
- Cosmetics
- Clean steam
- Pure steam
- SIP/CIP
- De-mineralised and reverse osmosis water



The range at a glance

STERI-TROL Model	Body pattern	Valve sizes	Flow type	Reduced flow and micro-flow options	Class VI soft seal option	FDA approved seals and USP26 Class VI	3 A's and EHEDG design	ASME BPE 2002 design	Material certificate EN 10204 3.1 supplied	Surface finish certificate option
SA	Angle pattern	DN15 to	Equal % Linear	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SH	Straight through	DN100	Fast opening							
SQ	Angle pattern	DN20 to DN100	Linear	No	Yes	Yes	Yes	Yes	Yes	Yes

Key features and benefits

rey leat	ures and t	Derients	
	Key features	Key reasons	Key benefits
	Self-draining	The angled design ensures self-draining of the valve. A precise radius is incorporated in the body design to eliminate dead zones.	There are no areas where the media can accumulate and create a potential for contamination.
	Crevice free	Mechanically polished to 0.4 microns as standard. Option of electro polish finish. Customer specified finish option.	A smooth finish promotes cleanliness and eliminates contamination from pyrogens.
	High performance stem sealing	A double stem seal is used to protect the valve from contamination and damage. One size stem seal for all sizes of valve.	Longer stem seal life and reduced maintenance. Less interruption to the process. Reduced spares stock holding.
	Quick release body and bonnet	A sanitary clamp is used to retain the body and bonnet connection.	The valve may be opened for inspection and maintenance quickly and easily, therefore minimising any process downtime.
	Long life actuator design	Developed from the proven Spirax Sarco rolling diaphragm actuator range with standard epoxy or ENP finish, or complete stainless steel construction.	Long actuator life and reduced maintenance. Less interruption to the process.
	Part of a total controls solution	One of many controls and instrumentation products that may be acquired separately	Peace of mind that your purchases are supported wherever you are in the world

from Spirax Sarco that may be acquired separately or as a complete one-stop-shop

controls solution.

wherever you are in the world, and that a single contract will fulfil

your controls requirement, from design to after sales service.

Group companies

Sales offices

Distributors

Africa

South Africa

Australia

Americas

Argentina	
Brazil	
Canada	
Mexico	

Asia

USA

China India Japan Korea Malaysia Singapore Taiwan Thailand

New Zealand

Australasia

Europe

Austria Belgium Czech Republic Denmark Finland France Germany

Italy Norway Poland Portugal Russia

Slovak Republic Spain Sweden Switzerland Turkey UK

Africa

Egypt Kenya Nigeria

Americas

Colombia Venezuela

Asia

Hong Kong Indonesia Pakistan Philippines Vietnam

Europe

Austria Hungary Ireland

Middle East

UAE

Some products, services or solutions may not be available in certain markets

Africa

Algeria Cameroon Ethiopia Ghana Ivory Coast Libya Malawi Mauritius Morocco Namibia Senegal Sudan

Tanzania Tunisia Uganda Zambia Zimbabwe

Americas

Bolivia Chile Colombia Costa Rica Dominican Republic Ecuador El Salvador Guatemala Honduras Jamaica

Nicaragua Panama Paraguay

Peru

Trinidad and Tobago

Uruguay Venezuela

Asia

Bangladesh

Australasia

Fiji

Europe

Bulgaria Croatia Cyprus Estonia Greece Iceland Latvia Lithuania Malta Netherlands Romania Slovenia

Middle East

Bahrain Iran Israel Jordan Kuwait Lebanon Oman Qatar Saudi Arabia Syria

Spirax-Sarco Limited Cheltenham UK **GL53 8ER** t: +44 (0)1242 521361 f: +44 (0)1242 573342 e: controls@uk.spiraxsarco.com www.spiraxsarco.com/controls

