



CH Issue 4


Cert. No. LRQ 0963008 ISO 9001


# 'C' Series **Valve Spares**

The spare parts available for the CE43, CE63 and CE83 valves, 1" to 8" (DN25 to DN200), are detailed below. No other parts are supplied as spares.

Available spares

Actuator clamping nut			Α	
Gland seal kit	PTFE seal set		В	
Giariu Sear Kit	Graphite	Graphite gasket Spacer Spiral wound gasket	С	
Valve plug			D	
Valve stem			Е	
Valve gasket kit	Bonnet	Graphite gasket	F1	
		Spacer	F2	
		Spiral wound gasket	F3	
	Seat		F4	
	Adaptor gasket		F5	
Piston seal kit	Graphite		G	
	PTFE		Н	
Valve seat			I	
Valve cage			J	
Reduction kit (seat, cage and reduction adaptor) K				
<b>Note:</b> A 'valve gasket kit' should be ordered with the above items.				





### Note:

When placing an order for spares please indicate clearly the model number, serial number and date code (found on the label of the valve body) to ensure that the order is processed quickly, efficiently and correctly.

# How to order spares

Always order spares by using the description given in the column headed 'Available spares'. Also state the information shown in the 'C' series valve selection guide, the serial number, and date code

# 'C' series valve selection guide

	<u>_</u>	
Valve size	1", 1½", 2", 2½", 3", 4", 5", 6" and 8" DN25, 40, 50, 65, 80, 100, 125, 150 and 200	2"
Valve series	C = Cage trim	С
Valve characteristic	E = Equal percentage F = Fast opening L = Linear M = Modified equal percentage	E
Body material	4 = Carbon steel 6 = Stainless steel 8 = Alloy steel	4
Connections	2 = Butt weld (2" to 8") 3 = Flanged 4 = Socket weld (1", 1½" and 2")	3
Stem sealing options	P = PTFE chevron H = Graphite B = Bellows	Р
Seating options	T = AISI 431 hardened G = PTFE soft seat W = Hard faced stellite AISI 316	Т
Type of trim	C = Standard cage P = Noise reducing perforated cage A = Anti-cavitation cage	С
Number of stages	1 = One 2 = Two 3 = Three her = To be specified	1
Trim balancing	B = Balanced U = Unbalanced	U
Bonnet type	S = Standard H = Extended for high temperature L = Extended for low temperature	S
Reduced trim	0 = No Reduction 1 = 1 Reduction 2 = 2 Reductions 3 = 3 Reductions	1
Cv	To be specified	C <sub>V</sub> 35
Connection type	ASME 300	
2" C E 4	3 PTC1US1 Cv35	ASME300

# How to order example

1 - Valve seat and valve gasket kit for a 2" CE43PTC1US1  $C_{\rm V}$ 35 valve, flanged to ASME 300, serial number FR00001. Date coded

# How to fit spares

Full instructions are given in the Installation and Maintenance Instructions supplied with the spare.